


## Products | Fuel transfer equipment

### Accessories



**Bottom fill dry break couplers for diesel/petrol and aviation fuels**



**Dry break couplers for ZVA nozzles (reusable)**



**Hose swivels 3/4", 1", 1 1/4", 1 1/2" and 2"**



**Hose connectors 3/4" and 1" with BSP and BSPT thread**



**Brass swage nipples with BSP thread available in the following sizes:**

- 3/4" bsp - 3/4" swage
- 3/4" bsp - 1" swage
- 1" bsp - 3/4" swage
- 1" bsp - 1" swage



**Automatic hose reels:**

- 3/4" with 12 metre hose
- 1" with 10 metre hose
- Also available without hose or shorter hose as standard.



**Goodyear Futura Flexsteel petroleum transfer hose 1", 3/4" and "**

With cover resists cracking and fading, designed to dispense a wide range of fuels with extreme durability. The wire braid construction provides excellent kink resistance, low computer creep, and long service life. UL 330 and CUL approved.

- Tube: Nitrile synthetic rubber (ORS)
- Cover: Futurin synthetic rubber (ORS)



**Aircraft refuelling hose (Wingcraft) and/or (Jetranger)**

For fuelling or defuelling commercial and private aircraft. It handles Jet A-1, Jet A and higher aromatic aviation gasoline. Its high working pressure permits use in fuel cart hydrant service. Hose meets API bulletin 1529-6<sup>th</sup> edition, 2005 and N.F.P.A. bulletin #407 (2007 revision).



**Aggie gas (farm tank hose) agriculture gasoline hose 1"**

Multi-use hose for dispensing gasoline, grease, kerosene and petroleum oils from farm and barrel type pumps. Ideal for gravity feed on diesel tanks. It is for agricultural, construction and industrial service where UL approval is not required.

## Products | Fuel transfer equipment

### Accessories



**Stainless steel calibrating can (prover) 20L**




**Petroleum manhole cover and collar**

- 16" manhole
- Pressure relief valve setting 3 psig
- Rated pressure actuated emergency venting: 375.000 cu.ft. per hour at 5 psig
- Not permitted on MC306 cargo tanks
- Certified and marked in accordance with 49CFR178.345-5
- Relief valve also serves as a 10" latch that can be easily opened for filling the tank or for inspection
- Cover: Plated steel
- Collar: Plated steel
- Gasket: Buna-N



**Fire extinguisher and wall bracket (9kg)**



**Earth cable and approved clamp for aviation fuelling and petrol transfer**



**A wide range of aluminium couplers**



**A wide range of aluminium couplers**



**A wide range of aluminium couplers**



**M.D. -212 encoder (ATEX)**

- 60 or 100 pulses per revolution
- Output 5-36 VDC
- Design to be used on dispenser meters



**J.S. -100 encoder**

- 100 pulses per revolution
- Output 8-24 VDC
- Design to be used on bulk industrial meters such as M40 and M50

## Products | Fuel transfer equipment

### Accessories



#### 15 litre drain pan (oil collector)

- Diameter: 500mm
- Height: 130mm



#### Farmer's Toolbox 1

- Size: 630 x 390 x 350mm (outside) and 550 x 310 x 290mm (inside)

#### Farmer's toolbox 2

- Size: 710 x 430 x 350mm (outside) and 625 x 350 x 290mm (inside)

#### Farmer's toolbox 3

- Size: 870 x 530 x 440mm (outside) and 790 x 450 x 370mm (inside)



#### Industrial Hose Reels

- 1" with 10 metre hose
- 1" with 15 metre hose
- 1 ½" with 15 metre hose
- Also available without hose or shorter hose as standard