

Products | Fuel transfer equipment

Fuel dispensers



ZC 22222-G

- Flow rate: 5-50L/min (Available in flow up to 80L/min)
- Nozzle: Auto shut-off
- Accuracy: $\pm 0.30\%$
- Repeating tolerance: $\leq 0.15\%$
- Inlet pressure: $\geq 54\text{kPa}$
- Outlet pressure: $\leq 0.3\text{MPa}$
- Voltage: 220V
- Explosion-proof signal: ExdmbIIAT3
- Dual nozzle and dual product



ZC 11111M

- Flow rate: 5-50L/min
- Nozzle: Auto shut-off
- Accuracy: $\pm 0.30\%$
- Repeating tolerance: $\leq 0.15\%$
- Inlet pressure: $\geq 54\text{kPa}$
- Outlet pressure: $\leq 0.3\text{MPa}$
- Voltage: 220V
- Explosion-proof signal: ExdmbIIAT3
- Single nozzle and single product



ZC 22222

- Flow rate: 5-50L/min (Available in flow up to 80L/min)
- Nozzle: Auto shut-off
- Accuracy: $\pm 0.30\%$
- Repeating tolerance: $\leq 0.15\%$
- Inlet pressure: $\geq 54\text{kPa}$
- Outlet pressure: $\leq 0.3\text{MPa}$
- Voltage: 220V
- Explosion-proof signal: ExdmbIIAT3
- Available in single nozzle single product and dual nozzle dual product