

Products | Fuel transfer equipment

Accessories



Bottom fill dry break couplers for diesel/petrol and aviation fuels



Dry break couplers for ZVA nozzles (reusable)



Hose swivels 3/4", 1", 1 1/4", 1 1/2" and 2"



Hose connectors 3/4" and 1" with BSP and BSPT thread



Brass swage nipples with BSP thread available in the following sizes:

- 3/4" bsp - 3/4" swage
- 3/4" bsp - 1" swage
- 1" bsp - 3/4" swage
- 1" bsp - 1" swage



Aggie gas (farm tank hose) agriculture gasoline hose 1"
Multi-use hose for dispensing gasoline, grease, kerosene and petroleum oils from farm and barrel type pumps. Ideal for gravity feed on diesel tanks. It is for agricultural, construction and industrial service where UL approval is not required.



Goodyear Futura Flexsteel petroleum transfer hose 1", 3/4" and 5/8"

With cover resists cracking and fading, designed to dispense a wide range of fuels with extreme durability. The wire braid construction provides excellent kink resistance, low computer creep, and long service life. UL 330 and CUL approved.

- Tube: Nitrile synthetic rubber (ORS)
- Cover: Futurin synthetic rubber (ORS)



Aircraft refuelling hose (Wingcraft) and/or (Jetranger)

For fuelling or defuelling commercial and private aircraft. It handles Jet A-1, Jet A and higher aromatic aviation gasoline. Its high working pressure permits use in fuel cart hydrant service. Hose meets API bulletin 1529-6th edition, 2005 and N.F.P.A. bulletin #407 (2007 revision).



Automatic hose reels:

- 3/4" with 12 metre hose
- 1" with 10 metre hose
- Also available without hose or shorter hose as standard.

Products | Fuel transfer equipment

Accessories



Stainless steel calibrating can (prover) 20L



Petroleum manhole cover and collar

- 16" manhole
- Pressure relief valve setting 3 psig
- Rated pressure actuated emergency venting: 375.000 cu.ft. per hour at 5 psig
- Not permitted on MC306 cargo tanks
- Certified and marked in accordance with 49CFR178.345-5
- Relief valve also serves as a 10" latch that can be easily opened for filling the tank or for inspection
- Cover: Plated steel
- Collar: Plated steel
- Gasket: Buna-N



Fire extinguisher and wall bracket (9kg)



Earth cable and approved clamp for aviation fuelling and petrol transfer



A wide range of aluminium couplers



A wide range of aluminium couplers



A wide range of aluminium couplers



M.D. -212 encoder (ATEX)

- 60 or 100 pulses per revolution
- Output 5-36 VDC
- Design to be used on dispenser meters



J.S. -100 encoder

- 100 pulses per revolution
- Output 8-24 VDC
- Design to be used on bulk industrial meters such as M40 and M50

Products | Fuel transfer equipment

Accessories



15 litre drain pan (oil collector)

- Diameter: 500mm
- Height: 130mm



Farmer's Toolbox 1

- Size: 630 x 390 x 350mm (outside) and 550 x 310 x 290mm (inside)

Farmer's toolbox 2

- Size: 710 x 430 x 350mm (outside) and 625 x 350 x 290mm (inside)

Farmer's toolbox 3

- Size: 870 x 530 x 440mm (outside) and 790 x 450 x 370mm (inside)